Analogue CCTV / HD 4n1 / Cameras / Dome Cameras

DS-2CE70KF0T-MFS(2.8mm)

HIKVISION



Features

- Hikvision
- Value Range
- HDTVI, HDCVI, AHD and CVBS Turret camera
- High Performance CMOS
- 3K (2960x1665)
- Output 4in1
- 2.8 mm Lens
- ColorVu: color image 24 hours
- 0 Lux
- White light range 20 m
- Audio over coaxial
- Integrated microphone
- 2D DNR
- Weatherproof IP67

Specifications

Brand	Hikvision
Range	Value
Image sensor	3K CMOS
Maximum resolution	3K (2960x1665) to 20 fps
Resolution	TVI: 3K (20 fps), 4Mpx (25~30 fps), 1080p (25~30 fps) CVI: 4 MP (25~30 fps) AHD: 5Mpx (20 fps), 4 Mpx (25~30 fps) CVBS: PAL/NTSC
Lens	2.8 mm
Viewing Angle (FOV)	102º (H), 56º (V), 122º (D)
Minimum illumination	0.001 Lux @ (F1.0, AGC ON) 0 lux with white light, 20 m range
Day / Night	ColorVu: color image 24 hours
Video output	1 x BNC switchable between HDTVI / HDCVI / AHD / CVBS
Video output switching	Via Switch
Audio	Built-in microphone (Audio via coaxial cable)
Basic functions	OSD menu (remote)
Configurable OSD functions	DWDR, BLC, HLC, 2DNR, AGC, AWB, Mirror function, Smart Light
Communication	HIKVISION-C
Lens Adjustment	3 Axis
Power supply	DC 12 V / 2.5 W max.
Degree of protection	Weatherproof IP67
Temp. operation	-40º C ~ +60º C
Material	Metallic
Dimensions	Ø 85.1 mm x 77.62 mm (H)
Base diameter	Ø base 85.1 mm / Ø entre tornillos 60 mm / 3 tornillos
Weight	328 g